



Main

Commercial Status	Commercialised
Range of product	Mini Pragma
Product or component type	Base
Accessory / separate part category	Enclosure accessory
[In] rated current	63 A
Number of horizontal rows	1
Number of 18 mm modules per row	12
Number of terminal blocks	1 neutral terminal block with 8 screw outgoers 1 earth terminal block with 8 screw outgoers
Terminal block function	Earth / neutral

Complementary

Enclosure mounting	Flush
Total number of 18 mm modules	12
Cable entry	Pre-cutted holes
Distribution block outgoers	4 x 10 mm ² for neutral 4 x 10 mm ² for earth 3 x 6 mm ² for neutral 3 x 6 mm ² for earth 1 x 16 mm ² for neutral 1 x 16 mm ² for earth
Enclosure material	Back part: technoplastic
Width	270 mm wall
Height	228 mm wall
Depth	80 mm wall

Environment

Standards	EN 50102 IEC 60695-2-11
Fire resistance	Back part : 650 °C
IK degree of protection	IK07
Ambient air temperature for operation	-25...60 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0901 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available Download Влияние На Продукта Върху Околната Среда
Product end of life instructions	Need no specific recycling operations